

SHEET 3.00



GENERAL MOTORS CORPORATION

MINOR BRAKE ADJUSTMENT


- 1. TURN BRAKE ADJUSTING SCREW (VIEW A) TO EXPAND BRAKE SHOES UNTIL A LIGHT UNIFORM DRAG IS FELT WHEN ROTATING DRUM WITH BOTH HANDS AT TIRE RADIUS.
- 2. TURN BRAKE ADJUSTING SCREW BACK TO CONTACT BRAKE SHOES, FOURTEEN NOTCHES OF STAR WHEEL SO AS TO INSURE RUNNING CLEARANCE AND GOOD FEEL AT BRAKE PEDAL.

MAJOR BRAKE ADJUSTMENT

- 1. LOOSEN ANCHOR PIN NUT ENOUGH TO ALLOW ANCHOR PIN TO SHIFT IN SLOT IN FLANGE PLATE WITHOUT TILTING.
- TURN BRAKE ADJUSTING SCREW (STAR WHEEL) TO EXPAND 2. BRAKE SHOES UNTIL A UNIFORM MODERATE DRAG IS FELT WHEN ROTATING DRUM. AT THE SAME TIME AS ADJUSTING SCREW IS BEING MOVED TO EXPAND SHOES, FLANGE PLATE SHOULD BE TAPPED LIGHTLY WITH HAMMER TO HELP ANCHOR PIN TO FIND THE CORRECT CENTER.
- TIGHTEN ANCHOR PIN NUT ENOUGH TO KEEP PIN SNUG BUT 3. NOT SO TIGHT THAT IT CAN NOT BE MOVED UP OR DOWN IN SLOT WITH LIGHT TAP OF HAMMER.
- 4. BACK OFF BRAKE ADJUSTING SCREW APPROX. TEN NOTCHES AND IF NECESSARY, TAP LIGHTLY UPWARD OR DOWNWARD ON ANCHOR PIN UNTIL . 010 FEELER CAN BE INSERTED AT BOTH HEEL & TOE OF SECONDARY FACING WITH EQUAL DRAG.
- TIGHTEN ANCHOR PIN NUT TO TORQUE OF 60 TO 80 LBS. FT. 5.
- RECHECK.010 CLEARANCE AT TOE & HEEL OF SECONDARY 6. SHOE IT MAY BE NECESSARY TO GO OVER STEPS 4 & 5 IF THE ANCHOR PIN NUT TIGHTENING CAUSES A SHIFTING OF THE CLEARANCE.
- REPLACE TIRE & WHEEL. 7.
- TURN BRAKE ADJUSTING SCREW TO EXPAND BRAKE SHOES 8. UNTIL A LIGHT UNIFORM DRAG IS FELT WHEN ROTATING DRUM WITH BOTH HANDS AT THE RADIUS.
- 9. TURN BRAKE ADJUSTING SCREW BACK TO CONTACT BRAKE SHOES FOURTEEN NOTCHES OF STAR WHEEL SO AS TO INSURE RUNNING CLEARANCE AND GOOD FEEL OF BRAKE PEDAL.

SEE LUBRICATION CHART SECTION 14

BRAKES




				1	
		2		1	
				in the	
				Carlo Carl	
				d grog	
DATE	SYM.	REVISION RECORD	AUTH.	DR.	

	NAME	CORVETTE INST	RUCTION MAN	NUAL	
	REF.	DRAWN O.W.	CHECKED N.D.	SECT.	SHEET
CK.	DATE 9-15-55	PART No. 372	6900	5	1.00



GENERAL MOTORS CORPORATION




BRAKE PEDAL & MAIN CYLINDER

11-13-56						NAME	CORVETTE INSTRUCTION MANUAL					
	3	PART ADDED	4059	v	F	REF.	DRAWN O.W.	CHECKED N.D.	SECT.	SHEET		
	2	WAS 103025			F					2.00		
10-11-56	1	WAS 100013	3729			DATE	PART No. 3726900		2.00			
DATE	SYM.	REVISION RECORD	AUTH.	DR.	CK.	9-15-55	3/	20900		Constant States		





÷.




SEE LUBRICATION CHART SECTION 14

FRONT BRAKE PIPES

UPDATED

and the second second




T						NAME	CORVETTE INST	NUCTION MAN	JAL	
				-	-	REF.			SECT.	SHEET
9-5-56		WAS 3696562	3818		F	1	O.W.	<u>N. D.</u>	5	3.00
7-31-56	1	REDRAWN & REVISED FOR 57	7616	-	1.	DATE 9-15-55		726900	-	
DATE	SYM.	REVISION RECORD	AUTH.	DR.	CK.	-10-00	1	in the second	1	1

PRIOR

CHEVROLET MOTOR DIVISION




GENERAL MOTORS CORPORATION



					Г
					-
			5010		-
7-31-56	1	REDRAWN & REVISED FOR 57	7616	-	-
DATE	SYM.	REVISION RECORD	AUTH.	DR.	



GENERAL MOTORS CORPORATION




	2	NOTE ADDED		⊢
9-5-56	1	WAS 3696562	3818	
DATE	SYM.	REVISION RECORD	AUTH.	DR

		NAME	CORVETTE I	NSTRUCTION	MANUAL	
	F	REF.	DRAWN O.W.	CHECKED L.S.	SECT.	SHEET
R.	CK.	DATE 9-15-55	PART No. 37	26900	5	4.00



GENERAL MOTORS CORPORATION



PARKING BRAKE ADJUSTMENT

TENSION ON BOTH CABLES MUST BE SUCH THAT WHEN CAR IS BROUGHT TO A FAST STOP FROM 15 M.P.H. BY APPLYING THE HAND BRAKE, ONE WHEEL WILL NOT SLIDE OR LOCK BEFORE THE OTHER BY MORE THAN 5 FEET WHEN CHECKED ON DRY CONCRETE PAVEMENT.

TO GUARD AGAINST TOO TIGHT OR TOO LOOSE ADJUSTMENT OF THE CABLES, THE PULL ON THE HAND BRAKE LEVER MUST BE 25-25 Lbs. AT 7 CLICKS OF THE RATCHETS. (THIS LOAD MUST BE NOTICEABLY AFFECTED BY ANY FRICTION IN THE HAND BRAKE SYSTEM.)


PARKING BRAKE LEVER SEE LUBRICATION CHART SECTION 14

						NAME CORVETTE INSTRUCTION MANUAL					
						REF.	DRAWN O.W.	CHECKED L.S.	SECT.	SHEET	
11-13-56	1	PART ADDED	4059	v	F	DATE	PART No.	726900	7 5	5 5.00	
DATE	SYM.	REVISION RECORD	AUTH.	DR.	CK.	9-15-55					

UPDATED



GENERAL MOTORS CORPORATION




PARKING BRAKE LINKAGE

						NAME CORVETTE INSTRUCTION MANUAL					
	3	WAS 120376		+	F	REF.	DRAWN	CHECKED	SECT.	SHEET	
	2	WAS 120214		1	1	1	0.W.	L. S.		1 1 00	
2-22-56	1	WAS 122027	5344	1		DATE	PART No.			6.00	
DATE	SYM.	REVISION RECORD	AUTH.	DR. C	CK.	9-15-55	A CHARGE	726900	Con Station State		

PRIOR CHEVROLET MOTOR DIVISION



GENERAL MOTORS CORPORATION



PARKING BRAKE LINKAGE

						NAME CORVETTE INSTRUCTION MANUAL						
			_			REF.	DRAWN O.W.	CHECKED L.S.	SECT.	SHEET		
						DATE	PART No. 3726900		5	6.00		
DATE	SYM.	REVISION RECORD	AUTH.	DR.	CK.	9-15-55						